



HP PUMPS (MAX 71 L/MIN & 350 BAR) XLTI SERIES

The Hawk plunger pumps from the XLTI series can be conceptually divided into two groups. The pumps from the first group are designed to reach a very high water pressure (maximum 300 bar): this type of pumps, thanks to the pressure performances, is mainly suitable for use on highperformance professional pressure washers. The pumps belonging to the second group instead can work with a high water flow rate (up to 54 l/min at 1450 rpm). The performances of this group of pumps make the XLTI suitable for use on automatic car wash gantries, on small vehicles used for urban cleaning services or on misting and firefighting systems.

FIELDS OF APPLICATION



TECHNICAL DATA

washer

Max pressure (bar)	300
Flow rate (I/min)	from 17 to 65
Manifold	brass
РТО	male shaft Ø 24 mm





PART NUMBERS

PN	RPM	FLOW RATE (L/MIN)	MAX PRESSURE (BAR)	MAX POWER (KW)	JIT Delivery
12XLT3020IS	1000-1200	30-36	200	11,5-13,8	
12XLT1530I	1450-1740	15-18	300	8,8-10,4	
12XLT1830I	1450-1740	18-22	300	10,1-12,1	
12XLT2230I	1450-1740	22-26	300	12,2-14,6	
12XLT2530I	1450-1740	25-30	300	14,1-16,2	
12XLT2730I	1450-1740	27-32	300	15,1-18,1	
12XLT3025I	1450-1740	30-36	250	14,2-17	
12XLT3325I	1450-1740	33-40	250	15,7-18,8	
12XLT3517I	1450-1740	35-42	170	11,2-13,4	
12XLT4017I	1450-1740	40-48	170	12,5-15	
12XLT4317I	1450-1740	43-52	170	14,1-16,9	
12XLT5015I	1450-1740	50-60	150	13,8-16,6	,
12XLT5415I	1450-1740	54-65	150	15,6-18,7	

MORE INFORMATION

- Brand: Hawk
- Available with right or left shaft (please specify in case of order)
- Atex certification available on request
- Made in Italy

